



BOND



BOND IT with SB-10 Paver Bond Proven Superior Strength Adhesive

- ✓ **Extreme Strength** – 900 psi which is **80% stronger** than most competing brands
- ✓ **Long Time Proven Performer** – used in commercial & residential projects for over 25 years
- ✓ **One Adhesive Does It All!** - pillar caps, retaining walls, pool coping, steps, outdoor kitchens, grill surrounds, paver installations and more
- ✓ **Apply in Extreme Weather Conditions** – Can be applied in below freezing temperatures and to frozen and/or wet block
- ✓ **Structural Grade Hardscape Adhesive** – Fast set up, quick curing, and superior strength
- ✓ **Another Superior Quality Product from SEK-Surebond** – Trust your entire project with SEK-Surebond’s line of hardscape installation accessories that have a long standing history of proven performance.



www.sek.us.com | 800-932-3343





SUREBOND

SB-10 Paver Bond

★ CONTRACTOR GRADE FOR RESIDENTIAL AND COMMERCIAL PROJECTS ★

USES

Ideal for concrete and clay pavers, steps, coping systems, seat walls, retaining walls and caps, columns and caps, outdoor kitchens, masonry and brick, natural and manufactured stone, and slate. Also bonds to other building materials such as treated lumber, aluminum foil back sheathing, gypsum, fiberglass and composite decking materials.

PRODUCT DESCRIPTION

SB-10 Paver Bond is a fast set up, quick curing, superior strength, structural grade adhesive. It will adhere well in extreme conditions such as temperatures ranging from 0° - 100°F, and frozen and/or damp substrates. SB-10's superior durability will withstand extreme wear and tear including heavy vehicular traffic. It helps to level and shim and can be applied easily with a caulking gun.

PREPARATION

For ultimate adhesion, surface should be clean, free from dirt, oil and grease, excessive water, ice or any other material. If cleaning is needed, prepare surface with SureClean Deep Penetrating Multi-Use Cleaner. Rinse thoroughly and let dry before applying SB-10 Paver Bond. Before application, inspect substrate to be sure it is structurally sound with no spalling, cracking or scaling. Check to make sure that the pavers or stones are smooth, flat and of the same height. **Because of SB-10 Paver Bond's quick set up time, dry fit all pieces to be adhered prior to applying SB-10.** Ensure proper drainage so that water does not collect or drain into adhered areas.

APPLICATION INFORMATION

Cut nozzle to desired size and puncture inner seal. Apply a 1/8" to 3/8" bead of SB-10 Paver Bond using a caulking gun. On most applications, apply SB-10 Paver Bond in a 'S' shape. Where there is a potential for moisture infiltration such as but not limited to concrete overlays on an existing step or sidewalk, apply multiple lines of SB-10 Paver Bond running in the same direction as the flow of drainage. Set in place and tamp gently with a rubber mallet to compress the adhesive. Positioning and aligning should be done within 10-15 minutes of application.

DRYING TIME SB-10 Paver Bond starts to set within 10-15 minutes. Full cure is achieved between 2 and 7 days depending on environmental conditions. At full cure, SB-10 Paver Bond is non-flammable and non-toxic.

CLEAN UP Use mineral spirits or chlorinated solvents following manufacturer's instructions and precautionary information.

COVERAGE*

10 fl. oz. cartridge - 1/8" Bead	103 linear feet
10 fl. oz. cartridge - 1/4" Bead	26 linear feet
10 fl. oz. cartridge - 3/8" Bead	13.5 linear feet
28 fl. oz. cartridge - 1/8" Bead	288 linear feet
28 fl. oz. cartridge - 1/4" Bead	86 linear feet
28 fl. oz. cartridge - 3/8" Bead	38 linear feet

*Actual coverage may vary depending on substrate type, age and condition, as well as application method.

APPLICABLE STANDARDS

UN-STD 1804, ASTM 2339-70, FHA UM-60

PACKAGING/SIZES

- Tenth Gallon Cartridges - (10 fl. oz.) packaged 12 per case, VOC <10 g/l, Tensile strength = 900 PSI
 - Quart Cartridges (28 fl. oz.) packaged 12 per case, VOC = <10 g/l, Tensile strength = 900 PSI

COLOR Sand.

SHELF LIFE One year.

STORAGE Store cartridges upright in a cool place. For ease of dispensing in cold weather, warm up tubes to approximately 50° F before use. Freeze-thaw stable. Rotate stock using older inventory first.

PRECAUTIONARY INFORMATION Highly flammable liquid and vapor until fully cured. Keep away from heat, sparks, open flames, hot surfaces - no smoking. Keep container tightly closed. No release into water. Use explosion-proof equipment and non-sparking tools. Take precautionary measures against static discharge. Wash thoroughly after handling. Wear protective gloves, eye protection, and face protection. (See Safety Data Sheet for complete information.)

EMERGENCY & FIRST AID MEASURES IF ON SKIN (OR HAIR): Take off immediately all contaminated clothing. If skin irritation occurs: Get medical attention. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. If eye irritation persists: Get medical attention. **IN CASE OF FIRE:** Use foam, dry chemical or carbon dioxide to extinguish. (See Safety Data Sheet for complete information.)

LIMITATIONS Do not use below grade, where water is always present or where there is direct contact with fire.

WARRANTY SEK-Surebond warrants its products to substantially conform to its published specifications at the time of purchase. The foregoing is the sole limited warranty applicable to the products. **SEK-SUREBOND HEREBY DISCLAIMS ALL OTHER WARRANTIES OF ANY KIND OR NATURE, WHETHER EXPRESS, IMPLIED, OR STATUTORY, INCLUDING WITHOUT LIMITATION THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ANY OTHER WARRANTY OTHER THAN THE WARRANTY SET FORTH ABOVE.** The user is solely responsible for determining suitability of the products for their particular use. While the actual application of this product is out of the control of SEK-Surebond, it is recommended that the application guidelines be followed completely and accurately. SEK-Surebond's liability for any damage shall not exceed the purchase price of the product used, and it shall have no liability for consequential, incidental or punitive damages.

ASSISTANCE & ADDITIONAL INFORMATION For sales, specification assistance, technical questions, detailing, etc., please contact:

3925 Stern Ave.
 St. Charles, IL 60174
 Email: info@sek.us.com
 Fax: 630-762-0607
800-932-3343
www.sek.us.com

