



# SUREBOND

TECHNICAL DATA SHEET

## SB-6000

Wet Look Sealer

★ CONTRACTOR GRADE FOR RESIDENTIAL AND COMMERCIAL PROJECTS ★

### USES:

Ideal for concrete and clay pavers, flat and stamped concrete or natural and manufactured stone. Also suitable for masonry, retaining walls, porous or unglazed tile and terrazzo. Not recommended for marble, granite or ceramic tile.

### PRODUCT DESCRIPTION:

**SB-6000 Wet Look Sealer** is a proprietary water-based, modified latex, exterior quality sealer. SB-6000 will seal and enhance the beauty of new and old surfaces with a luxurious, wet look sheen with pronounced color enhancement and satin finish. It is breathable and will not trap naturally occurring efflorescence, allowing it to be applied immediately after new paving stones are installed. SB-6000 improves surface durability and freeze-thaw resistance while protecting the surface from salt, acid and staining. It exceeds all VOC, EPA and OSHA standards. SB-6000 Wet Look Sealer has the consistency of water and is milky white when applied; it dries to a clear, wet look on the surface of the pavement. SB-6000 Wet Look Sealer can be used both inside and outside on old and new pavements. Cured sealer is freeze resistant to -60°F (-51°C) and is stable up to a temperature of 180°F (82°C).

Features	Benefits
<b>What makes SB-6000 Wet Look Sealer different?</b>	
<b>Enhances</b>	• Deepens & Enhances Surface Tone with Satin Finish
<b>Protective</b>	• Guards against Salt, Acid & Other Corrosives
<b>Stain Resistant</b>	• Promotes Easier Cleaning & Maintenance
<b>Breathable</b>	• Does Not Trap Moisture or Efflorescence
<b>Immediate Application</b>	• Can be Applied Immediately on New Paver Installations
<b>Low VOC</b>	• Environmentally Friendly, EPA Compliant Water Based Formula

### PRODUCTS FOR SEALING PREPARATION:

SureClean - Deep Penetrating Multi-Use Cleaner  
 SureStrip - Fast Acting Sealer Stripper  
 Efflo Off - Efflorescence, Mineral & Salt Deposit Cleaner  
 S.R.B. - Stain & Rust Buster  
 Oil Extractor - Oil Stain Cleaner

### PREPARATION: TEST FIRST

on a small inconspicuous area to determine the suitability and to verify if desired results are achievable with this product on your specific surface. If joint fill, such as PolySweep Polymeric Sand or properly graded jointing sand, will be installed in the pavement system, the joint fill material should be installed prior to sealing. The surface should be thoroughly clean and free from oil, dust, loose material, and previously applied sealer other than SB-6000 prior to sealer application. If needed, prepare surface with Surebond Cleaners before sealing. Thoroughly rinse all cleaner residue prior to sealing. Allow surface to dry for a minimum of 24 hours after cleaning and/or rain before sealer application. Use a leaf blower to remove dust, debris and fine sand particles from the surface before sealing. Cover/protect nearby landscape, vehicles and buildings from overspray during application.



### APPLICATION INFORMATION:

Apply when day and night temperatures are between 40°F - 95°F. Avoid windy conditions to keep sealer spray from drifting. NO pre-blending or mixing required. Do NOT dilute. SB-6000 can be applied by spraying or rolling on the surface. Using a handheld garden sprayer or foam roller, spray or roll on one light coat in the same direction over the entire area to be sealed. Once the first coat is dry to the touch (affected by humidity and temperature), spray or roll a second light coat in a cross direction to the first coat. The cross application will ensure a more uniform coverage. Use coverage guidelines to determine a sufficient amount of material to provide on each coat. Enough sealer should be applied to wet down and saturate all the pores on the paver surface, including the chamfers, edges and recessed areas on textured pavers. Care should be taken that no excess sealer is pooled on the surface or in the sand joints of the pavement. If necessary, back roll to remove the excess sealer with a foam roller. Material coverage will depend on the surface porosity and texture. NOTE: Excessive applications can cause surface to become slippery.

### DRY TIME:

Surface will be dry to touch within 60 minutes assuming 65-85°F at 50% relative humidity. Low surface or air temperature and or high relative humidity will extend dry times. Protect the surface from dust, rain, condensation and traffic while drying. Area can be open to foot & light vehicular traffic in 24 hours depending on site conditions. Full cure in 7 days under normal conditions.

### CLEAN UP:

For tools and equipment, use soap and water before product is allowed to dry.

TOLL FREE: 800-932-3343

www.sek.us.com



# SUREBOND®

## TECHNICAL DATA SHEET

# SB-6000

## Wet Look Sealer

★ CONTRACTOR GRADE FOR RESIDENTIAL AND COMMERCIAL PROJECTS ★

### MAINTENANCE/RE-APPLICATION:

Sealed surfaces should be properly maintained following SEK-Surebond's Restoration and Maintenance System guidelines to get the best long-term performance from both the pavement and SB-6000. Keep surface clear of buildup of dirt, grime and stains by rinsing with cold, clean water. If staining of surface does occur, Surebond sealers are compatible with Surebond multi-use and specialty cleaners which can be used to remove general dirtiness, organic and inorganic stains like oils, food and beverages and mineral deposits from the surface. Test cleaners in inconspicuous area prior to cleaning. Be sure to check dilution rates for all cleaners to determine if they are ready to use or to determine appropriate dilution rate especially for sealed surfaces. Efflorescence should be removed using Efflo Off and a pressure washer, in conjunction with agitation from a natural fiber brush. Care should be taken to ensure that excessive pressure is not utilized, as it may erode joint sand and could damage the surface itself. Thoroughly rinse all cleaner off the surface before sealing.

Depending on environmental conditions, a light reapplication may be required every 6 months to 2 years to maintain desired effect.

### PACKAGING/SIZES:

6 x 1 gallon containers per case  
5 gallon pails  
55 gallon drums  
Bulk packaging available

### COVERAGE\*:

MATERIAL	SQ FEET	SQ METERS
Pavers & Other Hardscape Surfaces	100 - 200	9.3 - 18.6
Concrete	150 - 250	13.9 - 25.2
Retaining Walls & Other Vertical Surfaces	100 - 200	9.3 - 18.6

\*Per Gallon. Two coats of SB-6000 are recommended. Allow first coat to dry before applying second coat. Second coat coverage is estimated between 200-300 sq. ft. per gallon (18.6-27.9 M/G). Actual coverage may vary depending on the type, age, condition, porosity of the surface, application method and other local conditions such as temperature & humidity.

**STORAGE:** Keep in a cool place. Do not allow to freeze.

**SHELF LIFE:** 2 years if properly stored

**VOC CONTENT:** <25 g/L

### LIMITATIONS:

Protect sealer from freezing and store in a cool place when not in use. In winter, keep in heated area. This sealer is not recommended for marble, granite, ceramic tile, and polished surfaces with a high gloss as they do not absorb the sealer. A test area is ALWAYS recommended to determine product suitability and compatibility with your specific

surface before use and to verify if desired results are achievable. Due to the inherent variability of natural stone and clay products, long term performance may vary. Please consult with SEK-Surebond prior to sealing if there are concerns. Never try to seal wet or damp surfaces. A minimum temperature of 40° (5°C) must be maintained for a period of 24 hours prior to application. Surface temperature should not exceed 95°F (35°C) during application.

### PRECAUTIONARY INFORMATION:

KEEP OUT OF REACH OF CHILDREN • Use only outdoors in a well ventilated area • Wear protective gloves, clothing, face and eye protection • Wash thoroughly after handling (See Safety Data Sheet for complete information.)

### EMERGENCY & FIRST AID MEASURES:

**IF ON SKIN:** Wash with plenty of soap and water. Take off contaminated clothing and wash before reuse. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if eye irritation persists. **IN CASE OF FIRE:** Use water, water fog, dry chemical, CO<sub>2</sub> or alcohol resistant foam to extinguish. (See Safety Data Sheet for complete information.)

### WARRANTY:

SEK-Surebond warrants its products to substantially conform to its published specifications at the time of purchase. The foregoing is the sole limited warranty applicable to the products. **SEK-SUREBOND HEREBY DISCLAIMS ALL OTHER WARRANTIES OF ANY KIND OR NATURE, WHETHER EXPRESS, IMPLIED, OR STATUTORY, INCLUDING WITHOUT LIMITATION THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ANY OTHER WARRANTY OTHER THAN THE WARRANTY SET FORTH ABOVE.** The user is solely responsible for determining suitability of the products for their particular use. While the actual application of this product is out of the control of SEK-Surebond, it is recommended that the application guidelines be followed completely and accurately. SEK-Surebond's liability for any damage shall not exceed the purchase price of the product used, and it shall have no liability for consequential, incidental or punitive damages.

### ASSISTANCE & ADDITIONAL INFORMATION:

For sales, specification assistance, technical questions, detailing, etc., please contact:



3925 Stern Ave.  
St. Charles, IL 60174  
Email: [info@sek.us.com](mailto:info@sek.us.com)  
Fax: 630-762-0607  
**800-932-3343**  
[www.sek.us.com](http://www.sek.us.com)

