



SUREBOND
PROTECTION THAT PAYS

SB-5000
STAIN BLOCKING SEALER

SUREBOND SEALERS

TECHNICAL DATA SHEET

PRODUCT DESCRIPTION:

SB-5000 Stain Blocking Sealer is a water-based fluorochemical dispersion that does not contain any silicone or wax components. It can be used indoors and outdoors, on old and new, horizontal or vertical surfaces. SB-5000 can be applied immediately after installation on most surfaces, as it is breathable and will not trap naturally occurring moisture or efflorescence. On new concrete, SB-5000 should be applied once concrete is fully cured (30 days after installation). SB-5000 provides an invisible and durable barrier against water, oil and organic staining which makes cleaning and maintenance easier. It is ideal for driveways, industrial flooring, building entrances, shopping malls, food courts, outdoor kitchens, garage floors and other surfaces at risk for staining. It is non-hazardous and VOC/EPA compliant. SB-5000 has the consistency of water, is milky white when applied and dries clear with a transparent finish. Cured sealer is freeze resistant to -60°F (-51°C) and is stable up to a temperature of 180°F (82°C).

FEATURES	BENEFITS
Stain Blocking	• Keeps Stains from Becoming Permanent
Semi-Penetrating Protection	• Superior Longevity & Durability
Non-Film Forming with Transparent Finish	• Does Not Alter the Appearance of the Surface
Breathable, Immediate Application	• Does Not Trap Moisture or Efflorescence

SUITABLE SURFACES:

Suitable for concrete and clay pavers, flat and stamped concrete, masonry, natural and manufactured stone, segmental retaining wall blocks, concrete walls and exposed aggregate. May be used on grout, unglazed tile and terra cotta. Safe to use on old or new surfaces in both inside and outside environments. Not recommended for granite, marble, asphalt, glazed or ceramic tile. Test first to verify performance and appearance before applying.

COVERAGE PER GALLON:

SURFACE TYPE	SQ FEET	SQ METERS
Pavers & Other Hardscape Surfaces	100 – 200	9.3 – 18.6
Concrete	150 – 250	13.9 – 25.2
Retaining Walls & Other Vertical Surfaces	100 – 200	9.3 – 18.6

Coverage based on single coat. Two coats applied wet-on-wet are recommended on surfaces that are new, porous or experience high level of traffic or staining. Actual coverage may vary depending on the type, age, condition, porosity of the surface, application method and other local conditions such as temperature & humidity.

PREPARATION:

TEST SEALER FIRST on a small inconspicuous area to determine suitability and if desired results are achievable with this product. Over application on some very dense substrates may slightly darken the surface or leave a white haze. On new concrete, SB-5000 should be applied once concrete is fully cured (30 days after installation). If joint fill will be installed, such as PolySweep polymeric sand or joint sand, install sand prior to sealing. Before sealing, surface should be thoroughly cleaned and prepared with Surebond Cleaners. For spot cleaning, use S.R.B. and/or Oil Extractor before cleaning the surface overall with SureClean. Use Efflo Off for efflorescence cleaning and SureStrip to remove previously applied sealer or curing compounds, other than SB-5000. Thoroughly rinse all cleaner residue from the surface. Allow surface to dry for a minimum of 24 hours after cleaning and/or rain before sealer application. Use a leaf blower to remove dust, debris and fine sand particles from the surface.

Cover/protect nearby landscape, vehicles and buildings from overspray during application.

APPLICATION INFORMATION:

Apply when day and night temperatures are between 40°F - 95°F. Maximum surface temperature should not exceed 120°F. Allow surface to dry for a minimum of 24 hours after cleaning and/or rain before sealer application. Avoid windy conditions to keep sealer spray from drifting. NO pre-blending or mixing required. DO NOT DILUTE. Two coats of SB-5000 are recommended on surfaces that are new, porous or experience high level of traffic or staining. On large projects, it may be necessary to work in smaller more manageable sections.

Application Tools: low pressure high volume sprayer, slit foam roller

Spray & Back Roll Application (Wet on Wet if applying two coats): Use coverage rate for your specific surface. Hold sprayer nozzle perpendicular to the surface, spray and overlap each spray pass. If desired, apply a second coat while the first coat is still wet ("wet on wet") and at a right angle to the first application. Do not allow surface to dry between coats. Use liberally but do not allow sealer to puddle. Before sealer dries, back-roll surface with a foam roller to eliminate any pooling and to even out the sealer. If applying two coats, only back roll once (after completing the second coat - while it is still wet).



SUREBOND
PROTECTION THAT PAYS

SB-5000
STAIN BLOCKING SEALER

SUREBOND SEALERS

TECHNICAL DATA SHEET

DRY TIME:

Surface will be dry to the touch within 60 minutes assuming 65-85°F at 50% relative humidity. Low surface or air temperature and/or high relative humidity will extend dry times. Protect the surface from dust, rain, condensation and traffic while drying. Area can be open to foot & vehicular traffic in 24 hours depending on site conditions.

CLEAN UP:

For tools and equipment, clean with soap and water before product is allowed to dry.

MAINTENANCE/RE-APPLICATION:

Sealed surfaces should be properly maintained following Surebond's Restoration and Maintenance guidelines to get the best long-term performance from both the pavement and SB-5000. To prevent build-up of dirt, grime and stains, rinse surface regularly with clean water. If stains do occur, Surebond cleaners are compatible with Surebond sealers. Consult cleaner instructions to determine if they are ready to use or if they require dilution. Test cleaners in an inconspicuous area prior to cleaning the entire surface. When using a pressure washer, do not use excessive pressure as it may erode joint sand and/or damage the surface. Thoroughly rinse the surface of cleaner residue.

SB-5000 re-application may need to be carried out every 5 - 10 years depending on the type of surface and environmental/site conditions.

PACKAGING:

Gallon Containers: 4 gallons/case, 36 cases/pallet
Five Gallon Pails: 36 pails/pallet
55 Gallon Drums: 4 drums/pallet
275 Gallon Totes

STORAGE: Store in original packaging in a cool, well-ventilated place. Do not allow to freeze.

SHELF LIFE: 2 years when unopened and properly stored

VOC CONTENT: < 300 g/L

PRECAUTIONARY INFORMATION:

Protect sealer from freezing and store in a cool place when not in use. In winter, keep in heated area. This sealer is not recommended for marble, granite, ceramic tile, and polished surfaces with a high gloss as they do not absorb the sealer. A test area is ALWAYS recommended to determine product suitability and compatibility with your specific surface before use and to verify if desired results are achievable. Due to the inherent variability of natural stone and

clay products, long term performance may vary. Please consult with SEK-Surebond prior to sealing if there are concerns. Never try to seal wet or damp surfaces. A minimum temperature of 40° (5°C) must be maintained for a period of 24 hours prior to application. Surface temperature should not exceed 120°F (49°C) during application. Work should cease in inclement weather (rain or strong wind).

KEEP OUT OF REACH OF CHILDREN • Use in a well ventilated area • Do not breathe vapors, spray or mist • Wear protective gloves, clothing, face and eye protection • Wash thoroughly after handling (See Safety Data Sheet for complete information.)

EMERGENCY & FIRST AID MEASURES:

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if feel unwell. **IF ON SKIN:** Wash with plenty of soap and water. Get medical attention if irritation occurs. Take off contaminated clothing and wash before reuse. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if eye irritation persists. **IN CASE OF FIRE:** Use water, water fog, dry chemical, CO₂, or alcohol resistant foam to extinguish. (See Safety Data Sheet for complete information.)

WARRANTY:

SEK-Surebond warrants its products to substantially conform to its published specifications at the time of purchase. The foregoing is the sole limited warranty applicable to the products. **SEK-SUREBOND HEREBY DISCLAIMS ALL OTHER WARRANTIES OF ANY KIND OR NATURE, WHETHER EXPRESS, IMPLIED, OR STATUTORY, INCLUDING WITHOUT LIMITATION THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ANY OTHER WARRANTY OTHER THAN THE WARRANTY SET FORTH ABOVE.** The user is solely responsible for determining suitability of the products for their particular use. While the actual application of this product is out of the control of SEK-Surebond, it is recommended that the application guidelines be followed completely and accurately. SEK-Surebond's liability for any damage shall not exceed the purchase price of the product used, and it shall have no liability for consequential, incidental or punitive damages.

SEK SUREBOND
HARDSCAPES *Done Right!*™

3925 Stern Ave. | St. Charles, IL 60174
Email: info@sek.us.com | 800-932-3343

