



**SUREBOND CLEANERS** **TECHNICAL DATA SHEET**

**PRODUCT DESCRIPTION:**

**SureStrip** is a technologically advanced stripper designed for removal of acrylics, acrylic latex, polyurethane and other resin coatings and sealers. It can also be used as a spot cleaner to remover paint spots. SureStrip is recommended for outdoor use only and works best on horizontal surfaces. SureStrip’s Clean Rinse Technology allows old sealer and stripper residue to be quickly and easily rinsed away with a low or high pressure washer. SureStrip is ready-to-use and should not be diluted. SureStrip will remove most Surebond film forming sealers. Not appropriate for use with SB-4000, SB-4400, SB-5000, SB-6400, SB-6700 and SB-6750.

FEATURES	BENEFITS
<b>Powerful Stripping Technology</b>	• Strips Away a Variety of Sealers and Coatings
<b>Fast Acting</b>	• Works in Minutes
<b>Safe For Most Surfaces</b>	• Does Not Damage or Etch Surfaces
<b>Ready To Use Formula</b>	• No Dilution Necessary
<b>Clean Rinse Technology</b>	• Sealer & Stripper Residue Rinses Away Easily

**SUITABLE SURFACES:**

Suitable for concrete and clay pavers, flat concrete, masonry, natural and manufactured stone, segmental retaining wall blocks, concrete walls and exposed aggregate. Can also be used on tile and terrazzo. Safe to use on surfaces in outside environments. Use caution on sensitive surfaces such as wet cast pavers and stamped concrete as it may cause damage to color of the surface. Not for use on asphalt. Test first to verify suitability and dwell time before stripping the entire surface.

**COVERAGE PER GALLON:**

APPLICATION	SQ FEET	SQ METERS
All Surfaces	125 - 250	11.6 – 23.2

**Coverage based on single treatment.** Some applications may require additional treatments. Coverage rate may vary depending on the surface porosity, texture, age or condition of sealer, application method and local conditions.

**PREPARATION/PRE-TESTING:**

Remove all loose soil and debris from the surface. Cover and protect adjacent and surrounding surfaces not intended to be stripped from old sealer, stripper and rinse water. Caution: SureStrip will remove paint from painted surfaces. Spray water on adjacent plants and grass to limit potential absorption of stripper. Cover

foliage with plastic sheeting or other proven protective material. It may be necessary to manage rinse water containing old sealer and stripper by reclamation to prevent run-off into storm sewer. Small scale projects can be dammed and residue removed with a shop vac. Large projects or volume of residue can be removed with a reclamation unit. **TEST FIRST:** Before using SureStrip, test on a small inconspicuous area following the application instructions to determine the suitability for removing the desired sealer from the surface. Allow test area to dry thoroughly before evaluating final appearance and results. Testing should confirm effectiveness of stripper and necessary dwell time.

**APPLICATION INFORMATION:**

Use SureStrip when air and surface temperatures are 40° F or above. If freezing conditions exist, allow time for the surface to thaw. If air temperatures exceed 90° F, flash cool the surface with water before applying product. Do not allow product to dry on a hot surface. Rinse thoroughly while stripper is still wet on the surface. Always perform a pre-test (refer to Pre-Test Instructions). On large projects, it may be necessary to work in smaller more manageable sections.

**Application Tools:** low-pressure high-volume sprayer, clean stiff bristle brush or broom, flat surface cleaner attachment (optional), cold pressure washer with 25° to 40° tip

**Application Instructions:** SureStrip is designed for one application stripping. Additional applications may be needed to remove some sealers. Do not dilute. Apply SureStrip using a low-pressure sprayer. If surface is sloped, apply SureStrip from bottom of slope working upwards using a side-to-side motion. Allow SureStrip to dwell for 10 – 15 minutes. Do not allow SureStrip to dry on the surface during dwell time. Re-apply SureStrip if necessary to keep the surface wet with product. Perform a test by scratching the sealer with a plastic putty knife to see if the sealer lifts from the surface. If sealer is gummy but not released, allow to dwell for an additional 10 minutes before re-testing. Re-apply SureStrip if starting to dry. Improve results by scrubbing surface with a brush, broom or flat surface cleaner to agitate and remove sealer. Rinse surface thoroughly with a cold water pressure washer or garden hose with nozzle. Only use as much pressure needed to thoroughly clean surface. Excessive high pressures can damage substrate. Before installing joint sand or sealing, allow surface to dry completely.

**CLEAN UP:**

Rinse all tools and overspray thoroughly with water before product dries.



**SUREBOND**  
PROTECTION THAT PAYS

**SureStrip**  
FAST ACTING  
SEALER STRIPPER

**SUREBOND CLEANERS**

**TECHNICAL DATA SHEET**

**PACKAGING:**

Gallon Containers: 4 gallons/case, 36 cases/pallet  
Five Gallon Pails: 36 pails/pallet  
55 Gallon Drums: 4 drums/pallet

**STORAGE:**

Keep container tightly closed in a cool, dry, well ventilated place. Opened containers must be carefully resealed and kept upright to prevent leakage. Do not allow to freeze.

**DISPOSAL:**

Dispose of contents and container to appropriate waste site or reclaimer in accordance with all applicable laws, regulations and product characteristics at time of disposal.

**SHELF LIFE:**

2 years when unopened and properly stored

**PRECAUTIONARY INFORMATION:**

**KEEP OUT OF REACH OF CHILDREN** • Read label and obtain special instructions before use • Do not handle until all safety precautions have been read and understood • Keep container tightly closed when not in use • Wash thoroughly after handling • Do not eat, drink or smoke when using this product • Wear protective gloves, clothing, face and eye protection • Avoid breathing mist, vapors or spray • Keep away from hot surfaces, sparks, open flames and other ignition sources • Use only outdoors in a well ventilated area • Avoid release to the environment (See Safety Data Sheet for complete information.)

**EMERGENCY & FIRST AID MEASURES:**

Get medical attention if exposed and you feel unwell, or are concerned. **IF INHALED:** Remove victim to fresh air and keep at

rest and keep comfortable for breathing. Call a **POISON CENTER** or physician if feel unwell. **IF SWALLOWED:** Immediately call a **POISON CENTER** or physician. Rinse mouth. Do NOT induce vomiting. **IF ON SKIN:** Take off contaminated clothing and wash before reuse. Wash skin with plenty of water or shower. If skin irritation occurs or you feel unwell get medical attention. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. **IN CASE OF FIRE:** Use water fog, dry chemical, CO<sub>2</sub> or alcohol resistant foam to extinguish. (See Safety Data Sheet for complete information.)

**WARRANTY:**

SEK-Surebond warrants its products to substantially conform to its published specifications at the time of purchase. The foregoing is the sole limited warranty applicable to the products. **SEK-SUREBOND HEREBY DISCLAIMS ALL OTHER WARRANTIES OF ANY KIND OR NATURE, WHETHER EXPRESS, IMPLIED, OR STATUTORY, INCLUDING WITHOUT LIMITATION THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ANY OTHER WARRANTY OTHER THAN THE WARRANTY SET FORTH ABOVE.** The user is solely responsible for determining suitability of the products for their particular use. While the actual application of this product is out of the control of SEK-Surebond, it is recommended that the application guidelines be followed completely and accurately. SEK-Surebond's liability for any damage shall not exceed the purchase price of the product used, and it shall have no liability for consequential, incidental or punitive damages.

**SEK SUREBOND**  
HARDSCAPES *Done Right!*<sup>™</sup>

3925 Stern Ave. | St. Charles, IL 60174  
Email: info@sek.us.com | 800-932-3343

