



SUREBOND CLEANERS

TECHNICAL DATA SHEET

PRODUCT DESCRIPTION:

AllStrip, a broad spectrum sealer stripper offered in spray and gel formulas, is designed for removal of acrylic, acrylic latex and polyurethane film forming sealers. It can also be used as a spot cleaner to remove paint spots. AllStrip is recommended for outdoor use only. The spray formula is most effective on horizontal applications. The gel formula can be used on both horizontal and vertical surfaces. AllStrip's Clean Rinse Technology allows old sealer and stripper residue to be quickly and easily rinsed away with a low or high pressure washer. AllStrip is ready-to-use and should not be diluted. Not appropriate for use with penetrating sealers.

FEATURES	BENEFITS
Reliable Stripping Performance	• Strips Away a Variety of Film Forming Sealers
Fast Acting	• Works in Minutes
Safe For Most Surfaces	• Does Not Damage or Etch Surfaces
Clean Rinse Technology	• Sealer & Stripper Residue Rinses Away Easily
Natural & Biodegradable	• Stripper Residue Breaks Down Quickly in Soil (Do not allow product to enter drains, sewers or waterways.)
Ready To Use Formula	• No Dilution Necessary

SUITABLE SURFACES:

Suitable for concrete and clay pavers, flat concrete, masonry, natural and manufactured stone, segmental retaining wall blocks, concrete walls and exposed aggregate. Safe to use on surfaces in outside environments. Use caution on sensitive surfaces such as wet cast pavers and stamped concrete as it may cause damage to color of the surface. Not for use on asphalt. **Test first** to verify suitability and dwell time before stripping the entire surface.

COVERAGE PER GALLON:

APPLICATION	SQ FEET	SQ METERS
All Surfaces	125 - 250	11.6 – 23.2

Coverage based on single treatment. Some applications may require additional treatments.

PREPARATION/PRE-TESTING:

Sweep and remove all loose soil and debris from the surface. Protect adjacent and surrounding surfaces not intended to be stripped from stripper, old sealer and rinse water. **Caution:** AllStrip will remove paint from painted surfaces. Spray water on adjacent plants and grass to limit potential absorption of stripper. Cover foliage with plastic sheeting or other proven protective material. It may be necessary to manage rinse water containing old sealer and stripper by reclamation to prevent run-off into storm sewer. Small scale projects can be dammed and residue removed with a shop vac. Large scale projects or large volume of residue can be removed with a reclamation unit.

Do not allow stripper and sealer residue to enter pools because it may cause a phosphorous reaction which will turn pool water green.

TEST FIRST: Before using AllStrip, test on a small inconspicuous area following the application instructions to determine the suitability for removing the desired sealer from the surface. Allow test area to dry thoroughly before evaluating final appearance and results. Testing should confirm effectiveness of stripper and necessary dwell time.

APPLICATION INFORMATION:

Use AllStrip when air and surface temperatures are 40° F or above. If freezing conditions exist, allow time for the surface to thaw. If air temperatures exceed 90° F, flash cool the surface with water before applying product. Do not allow product to dry on a hot surface. Rinse thoroughly while stripper is still wet on the surface. Always perform a pre-test (refer to Pre-Test Instructions). On large projects, it may be necessary to work in smaller more manageable sections.

AllStrip is designed to work with one application; however additional applications may be needed to completely remove some sealers. **Do not dilute.** For very difficult to remove sealers: It is recommended to apply a heavy coat of **AllStrip-Gel Formula** and let dwell for an extended period of time based on successful results from the pre-test.

Application Tools: low-pressure high-volume sprayer (spray formula), 1" nap roller (gel formula) clean stiff bristle brush or broom, cold pressure washer with 25° to 40° tip, flat surface cleaner attachment (optional).

Application Instructions: Apply AllStrip-Spray Formula using a low-pressure sprayer. If surface is sloped, apply from bottom of slope working upwards using a side-to-side motion. When using AllStrip-Gel Formula, apply with a 1" nap roller. Allow AllStrip to dwell for 15 - 30 minutes. Do not allow AllStrip to dry on the surface during dwell time. If necessary, re-apply AllStrip to keep the surface wet with product. After dwell time, perform a test by scratching the sealer with a plastic putty knife to see if the sealer lifts from the surface. If sealer is gummy but not released, allow to dwell for an additional 15 - 30 minutes before re-testing. Re-apply AllStrip if starting to dry. Improve results by scrubbing surface with a nylon brush to agitate and remove sealer. Do not apply water to the surface until ready to rinse because the stripping process will be interrupted. Rinse surface thoroughly with a cold water pressure washer with a 25° to 40° tip or rotating nozzle, flat surface cleaner attachment or a garden hose with nozzle. Only use as much pressure needed to thoroughly clean surface. Excessive high pressures can damage substrate. **Keep stripper and sealer from entering swimming pools.** It may be necessary to do a secondary application process to remove heavier sealers. After stripping and rinsing, if necessary, clean the substrate with SureClean following the instructions for proper dilution and application. Before installing joint sand or sealing, allow surface to dry completely to ensure all previously applied sealer has been completely removed.



SUREBOND
PROTECTION THAT PAYS

AllStrip
BROAD SPECTRUM
SEALER STRIPPER
GEL & SPRAY FORMULAS

SUREBOND CLEANERS

CLEAN UP:

Rinse all tools and overspray thoroughly with water before product dries.

PACKAGING:

Five Gallon Pails: 36 pails/pallet

STORAGE:

Keep container tightly closed in a cool, dry, well ventilated place. Opened containers must be carefully resealed and kept upright to prevent leakage. Keep in original packaging. Do not allow to freeze. Keep container with cap/lid tightly closed when not in use.

DISPOSAL:

Dispose of contents and container to appropriate waste site or reclaimer in accordance with all applicable laws, regulations and product characteristics at time of disposal.

SHELF LIFE:

2 years when unopened and properly stored

PRECAUTIONARY INFORMATION:

KEEP OUT OF REACH OF CHILDREN • Keep away from heat, hot surfaces, open flames and sparks. No smoking. • Keep container tightly closed when not in use • Ground/bond container and receiving equipment • Use explosion-proof electrical/ventilation/lighting equipment • Use only non-sparking tools • Take precautionary measures against static discharge • Do not breathe dust/gas/mist/vapor • Wash thoroughly with plenty of water and soap after handling • Do not eat, drink or smoke when using this product • Use only outdoors in a well ventilated area • Wear protective gloves, clothing and face/eye protection

TECHNICAL DATA SHEET

EMERGENCY & FIRST AID MEASURES:

IF EXPOSED OR CONCERNED: Get medical advice/attention. Call a POISON CENTER or doctor/physician. **IF SWALLOWED:** Rinse mouth. Immediately call a POISON CENTER or doctor/physician. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. **IF ON SKIN (or hair):** Wash with plenty of soap and water. Remove/take off all contaminated clothing. Rinse skin with water or shower. **IN CASE OF FIRE:** Use water spray (fog), alcohol resistant foam, dry chemical or Carbon Dioxide (CO₂).

See Safety Data Sheet for complete information.

WARRANTY:

SEK-Surebond warrants its products to substantially conform to its published specifications at the time of purchase. The foregoing is the sole limited warranty applicable to the products. **SEK-SUREBOND HEREBY DISCLAIMS ALL OTHER WARRANTIES OF ANY KIND OR NATURE, WHETHER EXPRESS, IMPLIED, OR STATUTORY, INCLUDING WITHOUT LIMITATION THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ANY OTHER WARRANTY OTHER THAN THE WARRANTY SET FORTH ABOVE.** The user is solely responsible for determining suitability of the products for their particular use. While the actual application of this product is out of the control of SEK-Surebond, it is recommended that the application guidelines be followed completely and accurately. SEK-Surebond's liability for any damage shall not exceed the purchase price of the product used, and it shall have no liability for consequential, incidental or punitive damages.

SEK SUREBOND
HARDSCAPES Done Right!™

3925 Stern Ave. | St. Charles, IL 60174
Email: info@sek.us.com | 800-932-3343

