

SUITABLE EXTERIOR SURFACES:

Concrete and clay pavers, flat concrete, masonry, natural stone, segmental retaining wall blocks, concrete walls and exposed aggregate. Can also be used on tile and terrazzo. Safe to use on surfaces in outside environments. Use caution on sensitive surfaces such as wet cast pavers, manufactured stone and stamped concrete as it may cause damage to color of the surface. Not for use on asphalt. Test first to verify suitability and dwell time before stripping the entire surface. SureStrip will remove most film forming sealers. Not appropriate for use with SB-4000, SB-4400, SB-5000, SB-6400, SurfacePRO Premium and SurfacePRO Ultra. Please consult with SEK-Surebond prior to stripping if there are concerns.

PREPARATION/PRE-TESTING:

Remove all loose soil and debris from the surface. Cover and protect adjacent and surrounding surfaces not intended to be stripped from old sealer, stripper and rinse water. Caution: SureStrip will remove paint from painted surfaces. Spray water on adjacent plants and grass to limit potential absorption of stripper. Cover foliage with plastic sheeting or other proven protective material. It may be necessary to manage rinse water containing old sealer and stripper by reclamation to prevent run-off into storm sewer. Small scale projects can be dammed and residue removed with a shop vac. Large projects or volume of residue can be removed with a reclamation unit. **TEST FIRST:** Before using SureStrip, test on a small inconspicuous area following the application instructions to determine the suitability for removing the desired sealer from the surface. Allow test area to dry thoroughly before evaluating final appearance and results. Testing should confirm effectiveness of stripper and necessary dwell time.

COVERAGE PER GALLON:

APPLICATION	SQ FEET	SQ METERS
All Surfaces	125-250	11.6-23.2

Coverage based on single treatment. Some applications may require additional treatments.

APPLICATION INFORMATION:

Always perform a pre-test (refer to Pre-Test Instructions). Use SureStrip when air and surface temperatures are 40° F or above. If freezing conditions exist, allow time for the surface to thaw. If air temperature exceeds 90° F, flash cool the surface with water before applying product. Do not allow product to dry on a hot surface. Rinse thoroughly while stripper is still wet on the surface. On large projects, it may be necessary to work in smaller more manageable sections.

Application Tools: low-pressure high-volume sprayer, clean stiff bristle brush or broom, cold or hot water pressure washer, flat surface cleaner attachment (optional)

CONTINUED

APPLICATION INFORMATION: CONTINUED

Application Instructions:

SureStrip is designed for one application stripping. Additional applications may be needed to remove some sealers. Do not dilute. Apply SureStrip using a low-pressure sprayer. If surface is sloped, apply SureStrip from bottom of slope working upwards using a side-to-side motion. Allow SureStrip to dwell for 10 – 15 minutes. Do not allow SureStrip to dry on the surface during dwell time. Re-apply SureStrip if necessary to keep the surface wet with product. Perform a test by scratching the sealer with a plastic putty knife to see if the sealer lifts from the surface. If sealer is gummy but not released, allow to dwell for an additional 10 minutes before re-testing. Re-apply SureStrip if starting to dry. Improve results by scrubbing surface with a brush, broom or flat surface cleaner to agitate and remove sealer. Rinse surface thoroughly with a cold water pressure washer or garden hose with nozzle. Only use as much pressure needed to thoroughly clean surface. Excessive high pressures can damage substrate. Before installing joint sand or sealing, allow surface to dry completely.

NOTE: Application of this product is out of the control of SEK-Surebond. Application steps should be followed completely and accurately. Should a problem occur with this product, SEK-Surebond limits liability to product replacement only. Buyer assumes all risk and liability resulting from the use or misuse of this product.

CLEAN UP: Rinse all tools and overspray thoroughly with water before product dries.

For complete & up to date information, refer to the technical data sheet found on www.sek.us.com.