

**SUREBOND SEALERS**

**TECHNICAL DATA SHEET**

**PRODUCT DESCRIPTION:**

**SB-6000 Wet Look Sealer** is a proprietary water-based modified-latex exterior quality sealer. It can be used indoors and outdoors, on old and new, horizontal or vertical surfaces to provide surface protection and enhancement. SB-6000 can be applied immediately after surface installation, as it is breathable and will not trap naturally occurring moisture or efflorescence. SB-6000 protects the surface from salts, acids and other corrosive chemicals as well as minimizes overall surface weathering and deterioration. On a newly installed or restored surface, SB-6000 will enhance surface tone with a wet look, satin finish and provide stain resistance which makes cleaning and maintenance easier. It is non-hazardous and VOC/EPA compliant. SB-6000 has the consistency of water, is milky white when applied and dries clear with satin finish. Cured sealer is freeze resistant to -60°F (-51°C) and is stable up to a temperature of 180°F (82°C).

FEATURES	BENEFITS
<b>Surface Enhancement</b>	<ul style="list-style-type: none"> <li>• Deeply Enhances Surface Tone</li> <li>• Satin Finish</li> </ul>
<b>Surface Protection</b>	<ul style="list-style-type: none"> <li>• Guards Against Salt, Acid &amp; Other Corrosives</li> </ul>
<b>Stain Resistant Water-Based Formula</b>	<ul style="list-style-type: none"> <li>• Promotes Easier Cleaning &amp; Maintenance</li> </ul>
<b>Breathable, Immediate Application</b>	<ul style="list-style-type: none"> <li>• Does Not Trap Moisture or Efflorescence</li> </ul>

**SUITABLE SURFACES:**

Suitable for concrete and clay pavers, flat and stamped concrete, masonry, natural and manufactured stone, segmental retaining wall blocks, concrete walls and exposed aggregate. May be used on porous or unglazed tile, terrazzo and terra cotta. Safe to use on old or new surfaces in both inside and outside environments. Not recommended for granite, marble, asphalt, glazed or ceramic tile. Test first to verify performance and appearance before applying.

**COVERAGE PER GALLON:**

APPLICATION	SQ FEET	SQ METERS
Pavers & Other Hardscape Surfaces	100 – 200	9.3 – 18.6
Concrete	150 – 250	13.9 – 23.2
Retaining Walls & Other Vertical Surfaces	100 – 200	9.3 – 18.6

**Coverage based on single coat. Two coats of SB-6000 are recommended.** Second coat is estimated between 200-300 sf per gallon (18.6 – 27.9 m/g). Actual coverage may vary depending on the type, age, condition, porosity of the surface, application method and other local conditions such as temperature & humidity.

**PREPARATION:**

**TEST SEALER FIRST** on a small inconspicuous area to determine suitability and if desired results are achievable with this product. Before sealing, surface should be thoroughly cleaned and prepared with Surebond Cleaners. For spot cleaning, use S.R.B. and/or Oil Extractor before cleaning the surface overall with SureClean. Use Efflo Off for efflorescence cleaning and SureStrip to remove previously applied sealer, other than SB-6000. Thoroughly rinse all cleaner residue from the surface. If installing joint sand/polymeric sand, install on a dry surface prior to sealing following manufacturer’s instructions. Allow surface to dry for a minimum of 24 hours after cleaning, polymeric sand activation and/or rain before sealer application. Prior to sealing, use a leaf blower to remove dust, debris and fine sand particles from the surface. Cover/protect nearby landscape, vehicles and buildings from overspray during application.

**APPLICATION INFORMATION:**

Apply when day and night temperatures are between 40°F - 95°F. Maximum surface temperature should not exceed 120°F. Allow surface to dry for a minimum of 24 hours after cleaning and/or rain before sealer application. Avoid windy conditions to keep sealer spray from drifting. NO pre-blending or mixing required. DO NOT DILUTE. It is recommended to apply two coats of SB-6000 following coverage guidelines. Excessive applications may decrease breathability and/or cause surface to become slippery. Some surfaces may require an anti-slip additive to increase friction.

**Application Tools:** low pressure high volume sprayer, slit foam roller

**Spray & Back Roll Application:** Use coverage rate for your specific surface. Hold sprayer nozzle perpendicular to the surface, spray and overlap each spray pass. Before sealer dries, back roll surface with a foam roller to eliminate any pooling and to even out the sealer. Once the first coat is dry to the touch (approximately 60 minutes - affected by humidity and temperature), apply a light second coat at a right angle to the first coat for more uniform coverage. Before sealer dries, back roll surface with a foam roller to eliminate any pooling and to even out the sealer.

**DRY TIME:**

Surface will be dry to the touch within 60 minutes assuming 65-85°F at 50% relative humidity. Low surface or air temperature and or high relative humidity will extend dry times. Protect the surface from dust, rain, condensation and traffic while drying. Area can be open to foot & vehicular traffic in 24 hours depending on site conditions. Full cure in 7 days under normal conditions.

**SUREBOND SEALERS**

**TECHNICAL DATA SHEET**

**CLEAN UP:**

For tools and equipment, clean with soap and water before product is allowed to dry.

**MAINTENANCE/RE-APPLICATION:**

Sealed surfaces should be properly maintained following Surebond's Restoration and Maintenance guidelines to get the best long-term performance from both the pavement and SB-6000. To prevent build-up of dirt, grime and stains, rinse surface regularly with clean water. If stains do occur, Surebond cleaners are compatible with Surebond sealers. Consult cleaner instructions to determine if they are ready to use or if they require dilution. Test cleaners in an inconspicuous area prior to cleaning the entire surface. When using a pressure washer, do not use excessive pressure as it may erode joint sand and/or damage the surface. Thoroughly rinse the surface of cleaner residue.

SB-6000 re-application may need to be carried out every 6 months to 2 years to maintain the desired level of enhancement depending on the type of surface and environmental/site conditions.

**PACKAGING:**

Gallon Containers: 4 gallons/case, 36 cases/pallet  
Five Gallon Pails: 36 pails/pallet  
55 Gallon Drums: 4 drums/pallet  
275 Gallon Totes

**STORAGE:** Keep in a cool, well-ventilated place. Do not allow to freeze.

**SHELF LIFE:** 2 years when unopened and properly stored

**VOC CONTENT:** < 25 g/L

**PRECAUTIONARY INFORMATION:**

Protect sealer from freezing and store in a cool place when not in use. In winter, keep in heated area. This sealer is not recommended for marble, granite, ceramic tile, and polished surfaces with a high gloss as they do not absorb the sealer. A test area is ALWAYS recommended to determine product suitability and compatibility with your specific surface before use and to verify if desired results are achievable. Due to the inherent variability of natural stone and clay products, long term performance may vary. Please consult with SEK-Surebond prior to sealing if there are concerns. The use of an anti-slip additive is recommended for increased traction on surface inclines or around consistently wet areas such as pool deck surrounds. Never try to seal wet or damp surfaces. A minimum temperature of 40° (5°C) must be maintained for a period of 24

hours prior to application. Surface temperature should not exceed 120°F (49°C) during application. Work should cease in inclement weather (rain or strong wind).

**KEEP OUT OF REACH OF CHILDREN** • Use in a well ventilated area • Wear protective gloves, clothing, face and eye protection • Wash thoroughly after handling (See Safety Data Sheet for complete information.)

**EMERGENCY & FIRST AID MEASURES:**

**IF SWALLOWED:** Call a **POISON CENTER** or physician if you feel unwell. **IF ON SKIN:** Wash with plenty of soap and water. Take off contaminated clothing and wash before reuse. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists get medical attention/advice. **IN CASE OF FIRE:** Use water, water fog, dry chemical, CO<sub>2</sub>, or alcohol resistant foam to extinguish. (See Safety Data Sheet for complete information.)

**WARRANTY:**

SEK-Surebond warrants its products to substantially conform to its published specifications at the time of purchase. The foregoing is the sole limited warranty applicable to the products. **SEK-SUREBOND HEREBY DISCLAIMS ALL OTHER WARRANTIES OF ANY KIND OR NATURE, WHETHER EXPRESS, IMPLIED, OR STATUTORY, INCLUDING WITHOUT LIMITATION THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ANY OTHER WARRANTY OTHER THAN THE WARRANTY SET FORTH ABOVE.** The user is solely responsible for determining suitability of the products for their particular use. While the actual application of this product is out of the control of SEK-Surebond, it is recommended that the application guidelines be followed completely and accurately. SEK-Surebond's liability for any damage shall not exceed the purchase price of the product used, and it shall have no liability for consequential, incidental or punitive damages.



624 W. Illinois Avenue, Aurora, IL 60506  
Email: info@sek.us.com | 800-932-3343

