Revision Date: 10.22.24 Page 1 of 16



SAFETY DATA SHEET

Section 1. Identification

Product Name: SB-10 Paver Bond Adhesive

Chemical Name: Mixture

General Description: Sealant/Adhesive

Supplier's Details: SEK-Surebond Corporation

624 W. Illinois Avenue Aurora, IL 60506 (800) 932-3343 www.sek.us.com

Emergency Telephone Number: CHEMTREC (800) 424-9300 (United States Only)

Chemtrec (outside USA): (703) 527-3887

Section 2. Hazards Identification

Physical Hazards:



HIGHLY FLAMMABLE LIQUID AND VAPOR – Category 2

Health Hazards:



SUSPECTED OF CAUSING CANCER – Category 2
SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD – Category 2



CAUSES SERIOUS EYE IRRITATION – Category 2A MAY CAUSE DROWSINESS OR DIZZINESS – Category 3

Revision Date: 10.22.24 Page 2 of 16

GHS Label Elements:

Hazard Pictograms:



Signal Word: Danger

Hazard Statements:

Highly flammable liquid and vapor
Causes serious eye irritation
Suspected of causing cancer
Suspected of damaging fertility or the unborn child
May cause drowsiness or dizziness

Reportable Ingredients for Labeling:

Naphtha (petroleum), solvent-refined light Toluene Acetone Kaolin

Precautionary Statements:

Prevention:

Keep out of reach of children. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. Ground/bond container and receiving equipment. No smoking. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/eye protection/face protection.

Response:

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO2, powder or spray.

Revision Date: 10.22.24 Page 3 of 16

Storage:

Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

Disposal:

Dispose of contents and container to appropriate waste site or reclaimer in accordance with all applicable laws, regulations, and product characteristics at time of disposal.

Classification system:

NFPA ratings (scale 0-4)

Health = 2 Fire = 3 Reactivity = 0

HMIS ratings (scale 0-4)

Health = 2 Fire = 3 Physical Hazard = 0

Hazards not otherwise classified:

Results of PBT and vPvB assessment: PBT: Not applicable vPvB: Not applicable

Section 3. Composition/Information on Ingredients

Information on Ingredients:

Chemical characterization: Mixtures

Description: Mixture

CAS NO.	SUBSTANCE	Content (wt. %)
79-20-9	Methyl acetate	25 - 50
67-64-1	Acetone	2.5 - 10
1330-20-7	Xylene	2.5 - 10
1333-86-4	Ethylbenzene	≤ 1.0
102-71-6	Triethanolamine	0- ≤ 0.5%
119-47-1	6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol	≤ 0.1%
111-42-2	2,2' -immeinodiethanol	0 - ≤ 0.09%

Revision Date: 10.22.24 Page 4 of 16

Section 4. First Aid Measures

If Inhaled:

Supply fresh air or oxygen; call for doctor. In case of unconsciousness, place patient stably in side position for transportation.

After Skin Contact:

Immediately wash with soap and water and rinse thoroughly.

After Eye Contact:

Rinse opened eye for 20 minutes under running water. Call a Doctor immediately.

After Swallowing (Ingestion):

Rinse mouth with water. Do not induce vomiting; immediately call for medical help.

Information for Doctor:

Most important symptoms and effects, both acute and delayed No further relevant information available.

Indication of any immediate medical attention and special treatment needed No further relevant information available.

Section 5. Firefighting Measures

Extinguishing Media:

Suitable extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray. Use firefighting measures that suit the environment.

Special hazards arising from the substance or mixture:

No further relevant information available.

Advice for firefighters:

Firefighters use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots and in enclosed spaces, SCBA.

Protective Equipment:

Protective clothing and respiratory protective device.

Revision Date: 10.22.24 Page 5 of 16

Section 6. Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures:

Wear protective equipment (see section 8). Keep unprotected persons away. Ensure adequate ventilation. See section 7 for safe handling.

Environmental Precautions:

Do not allow to enter sewers/surface or ground water. See section 13 for disposal information.

Methods and Material for Containment and Cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation. See

Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Section 7. Handling and Storage

Handling:

Precautions for Safe Handling:

- Avoid contact with skin and eyes.
- Ensure good ventilation/exhaustion at the workplace.
- Open and handle receptacle with care.
- Prevent formation of aerosols.

Precautions against Fire and Explosion:

- Keep container closed when not in use.
- Keep ignition sources away Do not smoke.
- Protect against electrostatic charges.

Conditions for safe storage, including any incompatibilities Storage:

- Store in a cool location away from direct heat.
- Store away from oxidizing agents.
- Keep receptacle tightly sealed.
- Store in cool, dry conditions in well-sealed receptacles.

Section 8. Exposure Controls/Personal Protection

Page 6 of 16

Additional information about design of technical systems: No further data; see item 7. Control Parameters:

Components With Limit Values That Require Monitoring at the Workplace

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

79-20-9 Methyl Acetate

PEL	Long-term value: 610 mg/m³, 200 ppm
REL	Short-term value: 760 mg/m³, 250 ppm
	Long-term value: 610 mg/m³, 200 ppm
TLV	Short-term value: 757 mg/m³, 250 ppm
	Long-term value: 606 mg/m³, 200 ppm

67-64-1 Acetone

PEL	Long-term value: 2400 mg/m³, 1000 ppm
REL	Long-term value: 590 mg/m³, 250 ppm
	Short-term value: 1187 mg/m ³ , 500 ppm
TLV	Long term value: 594 mg/m³, 250 ppm
	BEI

1330-20-7 Xylene

	- ,
PEL	Long-term value: 435 mg/m³, 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm
	Long-term value: 435 mg/ m³, 100 ppm
TLV	Short-term value: 651 mg/m³, 150 ppm
	Long term value: 434 mg/m³, 100 ppm
	BEI

1330-20-7 Ethylbenzene

PEL	Long-term value: 435 mg/m³, 100 ppm
REL	Short-term value: 545 mg/m ³ , 125 ppm
	Long-term value: 435 mg/ m³, 100 ppm
TLV	Short-term value: 651 mg/m³, 150 ppm
	Long term value: 87 mg/m³, 20 ppm
	BEI

102-71-6 Triethanolamine

T1.\/	1 1 1 5 1 - 3
ILV	Long-term value: 5 mg/m ³
	1 = 0.1.6 10.11.1 10.10.01 0 11.6/11.

Page 7 of 16

111-42-2 2,2' -immeinodiethanol

	Long-term value: 15 mg/m³, 3 ppm
TLV	Long-term value: 1*mg/m³, 0.2 ppm Skin; *inhalable fraction and vapor
	Skin; *inhalable fraction and vapor

Ingredients with Biological Limit Values:

67-64-1 Acetone

BEI	50 mg/L
	Medium: urine
	Time: end of shift
	Parameter: Acetone (nonspecific)

1330-20-7 Xylene

BEI	1.5 g/g creatinine
	Medium: urine
	Time: end of shift
	Parameter: Methylhippuric acids

1330-20-7 Ethylbenzene

	0.7 g/g creatinine
	Medium: urine
	Time: end of shift at end of workweek
	Parameter: Sum of mandelic acid and phenylglyoxylic acid
BEI	(nonspecific, semi-quantitative)
	_
	Medium: end-exhaled air
	Time: not critical
	Parameter: Ethyl benzene (semi-quantitative)

Additional Information: The lists that were valid during the creation were used as basis.

Exposure Controls:

Personal Proetctive Equipment (see listings below) General Protective and Hygienic Measures:

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes
- Avoid contact with the eyes and skin

Revision Date: 10.22.24 Page 8 of 16

Breathing Equipment:

Use approved respiratory protection equipment when airborne exposure is excessive. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations by the manufacturer.

Protection of Hands:

Protective Gloves:

The glove material has to be impermeable and resistant to the product/the substance/the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of Gloves: Nitrile rubber (NBR)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration Time of Glove Material: The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye Protection:

Safety glasses with side shields or tightly sealed goggles.

Body Protection:

Protective work clothing

Section 9. Physical and Chemical Properties

Information on Basic Physical and Chemical Properties:

Appearance:

Physical State/Form: Paste Color: Tan

Odor: Characteristic Odor Threshold: Not available

Safety Parameters:

Melting point/melting range:

Boiling point/boiling range:

Flash point:

Flammability (solid, gaseous):

Ignition temperature:

Undetermined

57° C (135° F)

-10° C (14° F)

Not applicable

455.0° C (851° F)

Page 9 of 16

Decomposition temperature: Not available.

Auto Igniting: Product is not self-igniting

Danger of Explosion: Product is not explosive. However, formation of explosive

air/vapor mixtures are possible.

Flammable Limits:

Lower: 3.1 Vol % Upper: 16.0% Vol %

Vapor Pressure at 20°C (68°F)

Specific Gravity at 20°C (68°F)

220hPa (165 mm Hg)

1.2 g/cm³ (10.014 lbs/gal)

Relative Density
Vapor Density
Not available
Evaporation Rate
Solubility in/Miscibility with Water:
Partition Coefficient (n-octanol/water):
Not available
Not available

Viscosity:

Dynamic Not available Kinematic: Not available

Solvent Content: 63.1%

Other Information: VOC – 75 f/L SCAQMD

Weight Per Gallon – 10.1 lbs/gal

Section 10. Stability and Reactivity

Reactivity:

Not reactive as supplied.

Chemical Stability

Stable under recommended storage conditions.

Thermal Decomposition/Conditions to be Avoided:

No decomposition if used according to specifications.

Possibility of Hazardous Reactions

No dangerous reactions known.

Conditions to Avoid

Heat, flames, sparks

Incompatible Materials:

Reacts with oxidizing agents.

Hazardous Decomposition Products:

Carbon monoxide and carbon dioxide

Revision Date: 10.22.24 Page 10 of 16

Section 11. Toxicological Information

Information on Toxicological Effects

Acute Toxicity:

Primary Irritant Effect:

On the skin: May irritate the skin.

On the eye: Causes serious eye irritation. Vapors may be irritating to the eyes. Irritating effect.

Sensitization: No sensitizing effects known.

Additional Toxicological Information: This product shows the following dangers according to internally

approved calculations methods for preparations: Irritant

Carcinogenic Categories

IARC (International Agency for Research on Cancer

1330-20-7	Xylene	3
100-41-4	Ethylbenzene	2B
9003-55-8	1,3-butadiene-styrene block polymer	3
102-71-6	Triethanolamine	3
111-42-2	2,2'-iminodiethanol	2B

NTP (National Toxicology Program)

None of the ingredients listed

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients listed

Section 12. Ecological Information

Toxicity

Aquatic toxicity: No further relevant information available. Persistence and degradability: No further relevant information available.

Behavior in Environmental Systems:

Bioaccumulative potential: No further relevant information available. Mobility in soil: No further relevant information available.

Additional Ecological Information:

General notes: At present there are no ecotoxicological assessments.

Page 11 of 16

Results of PBT and vPvB Assessment:

PBT: Not applicable. vPvB: Not applicable.

Other Adverse Effects: No further relevant information available.

Section 13. Disposal Considerations

Waste Disposal Method

Observe local/state/federal regulations. Uncleaned packaging should be treated with the same precautions as the material.

Section 14. Transport Information

UN-Number

DOT, IMDG, IATA: UN1133

UN Proper Shipping Name

DOT: Adhesives IMDG, IATA: ADHESIVES

Transport Hazard Classes

DOT:



Class: 3 Flammable Liquids

Label: 3

IMDG, IATA



Revision Date: 10.22.24 Page 12 of 16

Class: 3 Flammable Liquids

Label: 3

Packaging Group

DOT, IMDG, IATA:

Environmental Hazards Not applicable

Special Precautions For User

Hazard Identification Number

(Kemler code)EMS NumberStowage CategoryB

Transport in bulk according to Annex II

MARPOL 73/78 and IBC Code Not Applicable

Transport/Additional Information

49 CFR 173.150

Warning: Flammable Liquids

§ 173.150 Exceptions for Class 3 (flammable and combustible liquids).

- (a) General. Exceptions for hazardous materials shipments in the following paragraphs are permitted only if this section is referenced for the specific hazardous material in the § 172.101 Table of this subchapter.
- (b) LIMITED QUANTITIES. Limited quantities of flammable liquids (Class 3) and combustible liquids are excepted from labeling requirements, unless the material is offered for transportation or transported by aircraft, and are excepted from the specification packaging requirements of this subchapter when packaged in combination packagings according to this paragraph. For transportation by aircraft, the package must also conform to applicable requirements of § 173.27 of this part (e.g., authorized materials, inner packaging quantity limits and closure securement) and only hazardous material authorized aboard passenger-carrying aircraft may be transported as a limited quantity. A limited quantity package that conforms to the provisions of this section is not subject to the shipping paper requirements of subpart C of part 172 of this subchapter, unless the material meets the definition of a hazardous substance,

Revision Date: 10.22.24 Page 13 of 16

hazardous waste, marine pollutant, or is offered for transportation and transported by aircraft or vessel, and is eligible for the exceptions provided in § 173.156 of this part. In addition, shipments of limited quantities are not subject to subpart F (Placarding) of part 172 of this subchapter. Each package must conform to the packaging requirements of subpart B of this part and may not exceed 30 kg (66 pounds) gross weight. Except for transportation by aircraft, the following combination packagings are authorized:

- (1) For flammable liquids in Packing Group I, inner packagings not over 0.5 L (0.1 gallon) net capacity each, packed in a strong outer packaging;
- (2) For flammable liquids in Packing Group II, inner packagings not over 1.0 L (0.3 gallons) net capacity each, packed in a strong outer packaging.
- (3) For flammable liquids in Packing Group III and combustible liquids, inner packagings not over 5.0 L (1.3 gallons) net capacity each, packed in a strong outer packaging.

UN "Model Regulation"

UN 1133 ADHESIVES (Vapour pressure at 50°C not more than 110 KPA), 3 II

Section 15. Regulatory Information

Safety, Health and Environmental Regulations/Legislation Specific for The Substance Or Mixture:

SARA Section 355 (extremely hazardous substances):

None of the ingredients is listed.

SARA Section 313 (Specific toxic chemical listings):

1330-20-7 Xylene

100-41-4 Ethylbenzene

111-42-2 2,2'-iminodiethanol

TSCA (Toxic Substances Control Act):

All components of this product are on the TSCA Inventory or are exempt from TSCA inventory requirements.

Hazardous Air Polutants):

1330-20-7 Xylene

100-41-4 Ethylbenzene

111-42-2 2,2'-iminodiethanol

Revision Date: 10.22.24 Page 14 of 16

Proposition 65:

Chemicals known to cause cancer:

• 100-41-4 Ethylbenzene

Chemicals known to cause reproductive toxicity:

• None of the ingredients is listed

(DSL) Canada Domestic Substance List:

All components of this product are on the DSL (Canada Domestic Substance list) or are exempt from DSL requirements.

Carcinogenity Categories:

EPA (Environmental Protection Agency):

67-64-1 Acetone I
 1330-20-7 Xylene I
 100-41-4 Ethylbenzene D

TLV (Threshold Limit Value established by ACGIH):

• 67-64-1 Acetone	A4
• 1330-20-7 Xylene	A4
• 100-41-4 Ethylbenzene	А3
• 1332-58-7 Kaolin	A4
• 111-42-2 2,2'-iminodiethanol	А3

MAK (German Maximum Workplace Concentration):

• 100-41-4 Ethylbenzene	3A
• 111-42-2 2,2'-iminodiethanol	3B

NIOSH-Ca (National Institute for Occupational Safety and Health):

None of the ingredients is listed.

NATIONAL REGULATIONS:

Water Hazard Class:

Water hazard class 1 (self-assessment) slightly hazardous for water.

Chemical Safety Assessment:

A Chemical Safety Assessment has not been carried out.

Section 16. Other Information

Abbreviations & Acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

Revision Date: 10.22.24 Page 15 of 16

ICAO: International Civil Aviation Organization

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European

Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value
PEL: Permissible Exposure Level
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit

Flam Liq 2: Flammable liquids, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Carc. 2: Carcinogenicity, Hazard Category 2

LD50: Lethal dose, 50 percent

STOT SE 3: Specific target organ toxicity – Single exposure, Hazard Category

Revision Information: Not relevant.

Key Literature References

and Sources for Data: No data available.

Training Information: No data available.

Date of Issue/Date of Revision: 10.22.24

Notice to Reader

THE INFORMATION IN THIS SAFETY DATA SHEET (SDS) WAS OBTAINED FROM SOURCES WHICH WE BELIEVE ARE RELIABLE. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY WARRANTY, EXPRESSED OR IMPLIED, REGARDING ITS CORRECTNESS OR ACCURACY. SOME INFORMATION PRESENTED AND CONCLUSIONS DRAWN HEREIN ARE FROM SOURCES OTHER THAN DIRECT TEST DATA ON THE SUBSTANCE ITSELF. THIS SDS WAS PREPARED AND IS TO BE USED ONLY FOR THIS PRODUCT. IF THE PRODUCT IS USED AS A COMPONENT IN ANOTHER PRODUCT, THIS SDS INFORMATION MAY NOT BE APPLICABLE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION OR PRODUCTS

Revision Date: 10.22.24 Page 16 of 16

FOR THEIR PARTICULAR PURPOSE OR APPLICATION. THE CONDITIONS OR METHODS OF HANDLING, STORAGE, USE, AND/OR DISPOSAL OF THE PRODUCT ARE BEYOND OUR CONTROL AND MAY BE BEYOND OUR KNOWLEDGE. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR ANY LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH HANDLING, STORAGE, USE OR DISPOSAL OF THE PRODUCT.

SEK-Surebond is a registered trademark of SEK-Surebond Corporation.