

SUITABLE EXTERIOR SURFACES:

Suitable for concrete and clay pavers, flat concrete, masonry, natural stone, segmental retaining wall blocks, concrete walls and exposed aggregate in exterior environments. Use caution on sensitive surfaces such as wet cast pavers, manufactured stone and stamped concrete as color damage may occur. Not for use on asphalt. Always test first to verify suitability and required dwell time before stripping the entire surface. **AllStrip removes most acrylic, acrylic latex and polyurethane sealers. Not recommended for use with SB-4000, SB-4400 and SB-6400.**

PREPARATION/PRE-TESTING:

Remove all loose soil and debris from the surface. Cover and protect all adjacent surfaces not intended to be stripped from stripper, old sealer and rinse water. Caution: AllStrip will remove paint from painted surfaces. Protect foliage with plastic sheeting or other proven protective material. Rinse water containing old sealer and stripper may require reclamation to prevent run-off into storm sewers. Small projects can be dammed and residue removed with a shop vac, larger projects or higher volumes may require a reclamation unit. **Prevent excess sealer and residue from entering pools. TEST FIRST Before using AllStrip, test first** on an inconspicuous area following the application instructions to determine the suitability for removing the desired sealer from the surface. Allow test area to dry completely before evaluating final appearance and results. Testing should confirm effectiveness of stripper and necessary dwell time.

COVERAGE PER GALLON:

APPLICATION	SQ FEET	SQ METERS
All Surfaces	125-250	11.6-23.2

Coverage based on single treatment. Some applications may require additional treatments.

APPLICATION INFORMATION:

Always perform a pre-test (refer to Pre-Test Instructions). Apply AllStrip only when air and surface temperatures are 40° F or above; if freezing conditions exist, allow time for the surface to thaw. Do not apply if air temperatures exceed 90° F, and do not allow the product to dry on a hot surface. Rinse thoroughly while stripper is still wet. For large projects, work in smaller, more manageable sections.

Application Tools: low-pressure high-volume sprayer or 1" nap roller, clean stiff bristle brush or broom, cold water pressure washer with 25° to 40° tip, flat surface cleaner attachment (optional)

Application Instructions:

AllStrip is designed to work in a single application however additional applications may be required to completely remove some sealers. Do not dilute. Apply using a low pressure sprayer or roller. When spraying on sloped surfaces, apply from the bottom up using a side-to-side motion. Allow AllStrip to dwell for 15 – 30 minutes always keeping surface wet. Do not allow the product to dry; re-apply as needed. Test progress by scratching the sealer with a plastic putty knife.

CONTINUED

APPLICATION INFORMATION: CONTINUED

Application Instructions:

If the sealer becomes gummy but does not release, allow an additional 15 – 30 minutes of dwell time and re-test, re-applying if drying occurs. Scrubbing with a nylon brush may improve results. Do not apply water until ready to rinse, as this will interrupt the stripping process. Rinse surface thoroughly using cold water with a pressure washer (25° to 40° fan tip or rotating nozzle), flat surface cleaner or garden hose with nozzle. Use only as the pressure necessary – excessive pressure may damage the substrate. Heavier sealers may require a secondary stripping process. Allow surface to dry completely before installing joint sand or applying sealing

For difficult-to-remove sealers: Apply a heavy coat of AllStrip, cover the surface with plastic sheeting, and allow to dwell for an extended period (not to exceed 6–8 hours). No rain should be in the forecast during the dwell time. Block the area from vehicle and pedestrian traffic and turn off all irrigation systems. After the dwell time, remove the plastic sheeting. If the stripper has dried, apply a light coat of AllStrip and allow it to dwell for 30 minutes to re-wet the surface. Follow the rinsing instructions above.

NOTE: Application of this product is out of the control of SEK-Surebond. Application steps should be followed completely and accurately. Should a problem occur with this product, SEK-Surebond limits liability to product replacement only. Buyer assumes all risk and liability resulting from the use or misuse of this product.

CLEAN UP: Rinse all tools and overspray thoroughly with water before product dries.

For complete & up to date information, refer to the technical data sheet found on www.sek.us.com.